

# Sandvik QE442

## Free Flow tracked scalper

The QE442 Free Flow provides you with a versatile and highly efficient mobile solution for difficult to screen materials, without any of the plugging or blockages often experienced with traditional screens. It is your ideal solution for materials with a high fines content, such as soils, aggregates, ores, waste, biomass and other waste derived fuels including products with high moisture contents.



### Key benefits

#### Reliability

- Premium components selected throughout for maximum durability
- Proven reliability and high performance
- Capable of operating in the most hostile environments
- Heavy duty chassis designed to accommodate interchangeable side conveyors and compatible for 2-way or 3-way split configurations
- Large capacity wear resistant hopper with one-piece hopper design to minimize set-up time
- Feeder load sensing facility to prevent blockages and unnecessary downtime

#### Productivity

- Heavy duty top deck scalping screen allows you to process large un-screened material
- Aggressive Free Flow screen with wide range of adjustable throws and speeds enables the bottom deck to be tailored for numerous applications
- Dual motion Free Flow lower deck featuring polyurethane mats generates a huge throw and eliminates plugging and blockages
- Large stockpiling capability through integrated hydraulic conveyors
- User friendly PLC control system with sequential start-stop for speed and ease of set-up
- Choice of screen media to suit a wide range of applications
- Interchangeable side conveyors, which are compatible for 2-way or 3-way split operation
- Quick to set-up and easy to transport, resulting in more uptime and higher productivity
- Connected to Sandvik My Fleet with 7 year data subscription offering 24/7 fleet management, geo-fencing and remote operator support

#### Cost of ownership

- Latest generation fuel efficient engines provide maximum performance and cost efficiency
- Reduced fuel consumption through optimized hydraulic system and reduced engine RPM
- Well-proportioned fuel tank to maximize intervals between refueling
- Reduced cost of ownership through extended hydraulic fluid change intervals from 2000 hrs to 4000 hrs
- Hybrid "e" drive option with electric plug-in to run in diesel or electric mode for lower operating costs

#### Safety

- Mandatory audible and visual warning for safe operation whilst tracking and start-up / shut down
- Emergency stop buttons and conveyor pull stop cords around the plant for easy access during operation
- Wireless radio handset and two speed control for safe tracking onsite
- Hydraulically folding maintenance platforms provide safe access for service and maintenance
- Screen box jack up facility allows safe and easy access to the bottom deck for maintenance and media changes

#### Sustainability

- Latest emissions compliant engine lowers environmental impact due to reduced fuel consumption, less operating noise and low emissions
- 50% hydraulic fluid saving with extended service interval from 2,000 to 4,000 hours
- Hybrid "e" drive option reduces carbon emissions and minimizes fuel handling onsite

## Technical specification

Key specifications	QE442 Free Flow
<b>Hopper</b>	
Type	One-piece wear resistant
Width	3.14 m / 10' 3"
Length	5,72 m / 18' 8"
Capacity	8.5 m <sup>3</sup> / 11.1 yd <sup>3</sup>
<b>Feeder</b>	
Type	Heavy duty belt
Width	1300 mm / 51"
Belt speed (adjustable)	17 m / min (max)
<b>Oversize conveyor</b>	
Width	1600 mm / 63"
Discharge angle (adjustable)	18° to 25°
Discharge height (adjustable)	3.6 m / 11' 10" - 4.3 m / 14' 1"
<b>Side conveyor (midsize)</b>	
Width	900 mm / 36"
Discharge angle (adjustable)	18° to 25°
Discharge height (adjustable)	4.00 m / 13' 1"
<b>Side conveyor (fines)</b>	
Width	1000 mm / 39"
Discharge angle (adjustable)	20° to 25°
Discharge height (adjustable)	4.28 m / 14' 1"
<b>Transfer conveyor</b>	
Width	1400 mm / 55"
<b>Screen box</b>	
Top deck	4 off modular cassettes, side tension / bolted
Top deck screen size	5.39 m x 1.73 m / 17' 8" x 5' 8"
Top deck screen area	9.34 m <sup>2</sup> / 11 yrd <sup>2</sup>
Bottom deck	17 off polyurethane Free Flow mats, wedge fastened
Bottom deck screen size	5 m x 1.75 m / 16' 5" x 6'
Bottom deck screen area	9 m <sup>2</sup> / 10.7 yrd <sup>2</sup>
Variable screen angles	11° to 17°

Key specifications	QE442 Free Flow
<b>Tracks</b>	
Length (centres)	3.8 m / 12' 5"
Width (shoe)	500 mm / 20"
Control	Radio / Umbilical
<b>Power pack</b>	
Engine	CAT C4.4 Stage 5 / T4F 110 kW / 147 hp CAT C4.4 Stage 3A 98 kW / 132 hp
Diesel tank size	460 litres / 121.5 USG
Hydraulic tank size	400 litres / 105 USG
<b>Transport dimensions</b>	
Length	16.33 m / 53' 7"
Width	3.20 m / 10' 6"
Height	3.50 m / 11' 6"
Standard weight	37,587 kg / 82,865 lbs
<b>Operating dimensions</b>	
Length	16.82 m / 55' 2"
Width	14.56 m / 47' 9"
Height	4.68 m / 15' 4"
<b>Performance</b>	
Max feed size	200 mm <sup>3</sup> / 8"
Capacity (up to)	400 mtp <sup>h</sup> / 441 stph **
Travel speed	0.9 km/h / 0.55 mph slow 1.6 km/h / 1.0 mph fast
Max incline / Side to side	20° / 10°

Note. All weights and dimensions are for standard units only

## Standard specification

- Light mast and cabinet lights
- Radio control tracks 2 speed
- Hydraulic folding maintenance platforms
- Stabilizing legs
- Wear resistant liners in hopper and both side conveyor feed boots
- Toughflex belt

- Variable speed feed conveyor
- 3 hydraulic folding discharge conveyors
- Heavy duty bearings
- Pull stop cords on all conveyors \*
- Dust suppression spray bars \*
- My Fleet telematics with 7 year data subscription

\* Variant dependent \*\* Application specific. Please contact a Sandvik representative for clarification on specifications and options  
Sandvik reserves the right to make changes to the information on this data sheet without prior notification to users